

## Technical Data

Solid state transistor powered bass amplifier combo, 19" rack mountable, 2 rackspaces high.

### Inputs

- 1 Jack (1/4") A for passive basses and active basses with low output level
- 1 Jack (1/4") B for active basses, additional pre-damping control

### Equalization

Bass	+/- 15dB	60Hz
Low	+/- 12dB	130Hz
Mid	+/- 8dB	550Hz
High	+/- 12dB	4.2kHz
Treble	+/- 15dB	12kHz

### Outputs

- 1 Tune Send Jack 1/4"
- 1 Pre-Amp Out Jack 1/4"
- 1 Balanced DI Out XLR, with level control, pin 1 ground, pin 2 signal+, pin 3 signal -
- 2 Speakers Speakon, pin 1+ and 2+ signal hot, pin 1- and 2- signal cold

### Effects

- 1 Serial Loop, pre eq
- 1 Parallel Loop, post eq, with mix feature (0-100%) and footswitch activation.

### Switches

- 1 Tune (cancels all outputs without Tune Send)
- 1 Input A/B (activates Input A or B)
- 1 Eq On
- 1 Effect On
- 1 Power On
- 1 Ground Lift
- 1 DI pre/post Eq
- 1 Footswitch jack Tune On
- 1 Footswitch jack Effect On

### Special Features

- LED Peak Indicators for Pre-Amp and Power Amp
- LED Indicators for all switch functions
- Built in A/B box with separate damping control for Input B

Output power:	250 watts@4 ohms, 135 watts@8 ohms
Frequency range:	20 Hz to 25 KHz -1dB
Power requirement:	230V AC, 2A Slo / US-Version 117 AC, 4A Slo
Dimensions:	483 mm x 88 mm x 298 mm (19 x 3,5 x 11,8")
Weight:	9 kg (20 lbs)

### Combo Box

1x12" speaker with adjustable tweeter

Powerhandling:	300 Watt / 4 or 8 ohms
Frequency range:	39 Hz – 18 KHz
Sensitivity:	98 dB/1 W/1 m
Dimensions:	540 x 530 x 375 mm (21,2 x 20,8 x 14,8")
Weight incl. amp:	28 kg (62 lbs)